

TACAN NTU Chan 113	APCH CRS 309°	Rwy ldg 32L 8000 32R 8001
		TDZE 32L 22 32R 20
		Arpt Elev 22

[USN]

OCEANA NAS (APOLLO SOUCEK FLD) (KNTU)

TACAN Y RWY 32L/R

✦ * When ALS inop, increase CAT AB vis to 1 mile,
CAT CD vis to 1¼ miles.


ALSF-1
A1

MISSED APPROACH: Climbing left turn to 3000,
intercept NTU TACAN R-223 to GRAIT and hold.

ATIS 317.6	APP/DEP CON 123.9 266.8	TOWER 127.075 360.2	GND CON 119.6 336.4	CLNC DEL 254.4	ASR/ PAR
---------------	----------------------------	------------------------	------------------------	-------------------	-------------

Knots	60	120	180	240	300	360
V/V(fpm)	220	440	660	880	1100	1320
ATC climb of 220 ft/NM to 3000						

CAUTION:
Rwy 32L final approach crs 171° from rwy cntrln at 3000' from thld.
Rwy 32R final approach crs 528° from rwy cntrln at 3000' from thld.



EMERG SAFE ALT 100 NM 6100

ELEV 22

TDZE 32L 22
TDZE 32R 20

CATEGORY	A	B	C	D
S-32L *	460-1½	438 (500-½)	460-¾	438 (500-¾)
S-32R	460-1	440 (500-1)	460-1¼	440 (500-1¼)
CIRCLING	500-1	478 (500-1)	600-1½ 578 (600-½)	600-2 578 (600-2)

TACAN Y RWY 32L/R