

LOC I-RUQ

109.95

APP CRS

202°

Rwy Idg

5501

TDZE

772

Apt Elev

772

ILS or LOC RWY 20

MID-CAROLINA RGNL (RUQ)

ADF required. When local altimeter setting not received, use Lexington altimeter setting and increase all DA 37 feet and all MDA 40 feet; increase S-LOC Cats C/D visibility 1/8 SM and Circling Cat D visibility 1/4 SM. For inop ALS when using Lexington altimeter setting, increase S-LOC 20 Cats C and D visibility to 1 3/4 mile.

MALSR

MISSED APPROACH: Climb to 1600 then climbing right turn to 2900 direct ROVDY LOM and hold.

AWOS-3

118.175

CHARLOTTE APP CON

128.325 307.8

CLNC DEL

127.35

UNICOM

122.725 (CTAF) 1

ADF REQUIRED

BARRETT'S MOUNTAIN

113.75 BZM

Chan 84(Y)

2323

A

3900

108°

(37.5)

1730

A

MOPED CLT

22.9

3400

071°

(22.5)

1848

A

1060

A

988±

A

822

A

1051

A

964

A

1453

A

1121

A

LOM/IAF

ROVDY

275 RU

LOCALIZER 109.95

I-RUQ

GREENSBORO

116.2 GSO

Chan 109

2900

236°

(31.3)

AZELL INT

GSO

17

ALTERNATE MISSED

APCH FIX

AZELL INT

GSO

17

116.2 GSO

R-231

Chan 109

113.0 LIB

R-278

Chan 77

MSA RU 25 NM

3400

ELEV 772

TDZE 772

202°

02°

5501 X 100

MIRL Rwy 2-20

REIL Rwys 2 and 20

FAF to MAP 5 NM

Knots

60 90 120 150 180

Min:Sec

5:00 3:20 2:30 2:00 1:40

1600

2900

ROVDY

ROVDY RU LOM

2422

022°

2500

202°

2500

GS 3.00°

TCH 46

5 NM

CATEGORY	A	B	C	D
S-ILS 20	972-1/2		200 (200-1/2)	
S-LOC 20	1360-1/2 588 (600-1/2)		1360-1/4 588 (600-1/4)	
CIRCLING	1360-1 588 (600-1)		1440-1 3/4 668 (700-1 3/4)	1440-2 668 (700-2)

SALISBURY, NORTH CAROLINA

Amdt 1C 27FEB20

35°39'N-80°31'W

MID-CAROLINA RGNL (RUQ)

ILS or LOC RWY 20