

WAAS CH 69322 W03A	APP CRS 031°	Rwy Idg TDZE 1248 Apt Elev 1270
--	------------------------	---


RNAV (GPS) RWY 3

FOOTHILLS RGNL (MRN)

⚠ Baro-VNAV NA when using Hickory altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 36°C (96°F). DME/DME RNP-0.3 NA. VDP NA with Hickory altimeter setting. When local altimeter not received use Hickory altimeter: increase LPV DA to 1540 feet, LNAV/VNAV DA to 1600 feet, and visibility LNAV/VNAV all Cats ¼ SM; increase all MDA 60 feet and visibility LNAV Cats C and D ¼ SM and Circling Cat D ¼ SM.

MISSED APPROACH:
Climb to 4800 direct
CIKIS and hold.

AWOS-3P 124.175	ATLANTA CENTER 125.15 263.0	UNICOM 122.7 (CTAF) 0
---------------------------	---------------------------------------	---------------------------------



ELEV 1270		TDZE 1248	
MIRL Rwy 3-21 0			
REIL Rwy 3 and 21 0			

5 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 66).

GONGE CETAM BUNNA CAYAB 2.1 NM to RW03

GP 3.00° TCH 45

4700 211° 031° 4200 031° 3300 1940 1 NM to RW03

*1 NM to RW03

*1940

4800 CIKIS

*LNAV only

3500 X 75

0.7% UP

031°

CATEGORY	A	B	C	D
LPV DA	1498-1		250 (300-1)	
LNAV/VNAV DA	1558-1½		310 (300-1½)	
LNAV MDA	1620-1		372 (400-1)	
CIRCLING	1720-1 450 (500-1)	1760-1 490 (500-1)	1800-1½ 530 (600-1½)	2140-2¾ 870 (900-2¾)