


WAAS CH 45725 W13A	APP CRS 135°	Rwy Idg TDZE Apt Elev	5500 804 814
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

CANANDAIGUA (IUA)

RNP APCH-GPS.			MISSED APPROACH: Climb to 1300 then climbing right turn to 4000 direct UMAGY and hold, continue climb-in-hold to 4000.
Baro-VNAV and VDP NA when using ROC altimeter setting. Rwy 13 helicopter visibility reduction below ¼ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use ROC altimeter setting and increase LPV DA to 1138 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1333 feet and all visibilities ½ SM. Increase all MDAs 100 feet and LNAV visibility Cat C ¾ SM, and Circling visibility Cat C ½ SM.			
AWOS-3P 118.675		ROCHESTER APP CON 119.55 269.6	UNICOM 122.8 (CTAF) 0



4 NM Holding Pattern		CAMEY		MCANN		TUDDO 2 NM to RW13		UMAGY		
3200		315° 135°		2400		1460		1300 4000 △		
GP 3.00° TCH 40		2400		2400		1.1 NM to RW13		RW13		
		6.6 NM		2.9 NM		0.9 NM		1.1 NM		
CATEGORY	A	B		C		D				
LPV DA	1056-1		252 (300-1)		NA					
LNAV/VNAV DA	1251-1¾		447 (500-1¾)		NA					
LNAV MDA	1180-1		376 (400-1)		NA					
CIRCLING	1460-1		646 (700-1)		1540-2 726 (800-2)		NA			
MIRL Rwy 13-31 REIL Rws 13 and 31										