

SAN ANTONIO INTL (SAT)(KSAT) 7 N UTC-6(-5DT) N29°32.04' W98°28.14'

SAN ANTONIO

809 B LRA ARFF Index—See Remarks NOTAM FILE SAT

H-7B, L-19C

RWY 04-22: H8505X150 (CONC-GRVD) S-95, D-190, 2S-175, 2D-270 PCR 924 R/B/W/T HIRL CL

IAP, AD

RWY 04: MALS. PAPI(P4R)—GA 3.0° TCH 79'. RVR-T Pole. 0.3% down.

RWY 22: REIL. PAPI(P4L)—GA 3.0° TCH 85'. RVR-R 0.5% up.

RWY 13R-31L: H8502X150 (CONC-GRVD) S-95, D-190, 2D-270 PCR 818 R/B/W/T HIRL CL

RWY 13R: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 75'. RVR-TMR

RWY 31L: MALSR. PAPI(P4L)—GA 3.0° TCH 82'. RVR-TMR Bldg.

RWY 13L-31R: H5519X100 (ASPH) S-59, D-120 PCR 529 F/C/X/T MIRL

RWY 13L: REIL. PAPI(P4L)—GA 3.0° TCH 40'.

RWY 31R: REIL. PAPI(P4L)—GA 3.0° TCH 60'.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04: TORA-8505 TODA-8505 ASDA-8505 LDA-8505

RWY 13L: TORA-5519 TODA-5519 ASDA-5519 LDA-5519

RWY 13R: TORA-8502 TODA-8502 ASDA-8502 LDA-8502

RWY 22: TORA-8505 TODA-8505 ASDA-8505 LDA-8505

RWY 31L: TORA-8502 TODA-8502 ASDA-8502 LDA-8502

RWY 31R: TORA-5519 TODA-5519 ASDA-5519 LDA-5519

SERVICE: S4 **FUEL** 100LL, JET A **OK** 1, 2, 3, 4

NOISE: Noise sensitive areas exist on all sides of apt, at pilots discretion climb as quickly and quietly as safely possible on departure and use consideration when flying over populated areas by minimizing flt and high pwr settings. Military aircraft: Departing and arriving aircraft will use minimum power settings consistent with aircraft flight manuals, afterburner takeoff is prohibited unless required for safety of flight. Engine run-ups are permitted btr 1200-0500Z.

AIRPORT REMARKS: Attended continuously. Numerous flocks of birds invof apt. Glider/soaring ops aprx 17 miles northwest of apt dur VFR. Class I, ARFF Index C. SAT is ARFF Index C; ARFF Index D avbl with PPR. Rwy 13L-31R not avbl part 121 for air carrier ops. Foreign mil acft with wingspans less than 100' must report to general aviation ramp federal inspection station for cstsms processing, ctc apt mgmt at 210-207-3433. Arpt restricted to acft with wingspan greater than 171', PPR with 24hr OPS 210-207-3433. Rqrnd for auth. PPR with apt ops for acft powering back from terminal gates. Acft taxiing on Rwy 04 northeast bound look for hold short to Rwy 31L. Acft taxiing on Twy N southwest bound look for hold short to Rwy 31R. Apron East Cargo Ramp intersection of Rwy 04-22 and Twy D aircraft are requested to apply the minimum thrust when crossing the rwy to avoid damage due to jet blast. The following twys are not avbl for acft 59000 lbs or over: Twy A, Twy M, Twy H northwest of Twy Z and Twy E east of Rwy 04-22. Inner ramp taxilane north of Terminal A and B is clsd to acft with wingspan greater than 135'. Acft at Terminal A and B advise grid ctly prior to push. Twy L clsd northbound. Twys L and B clsd to acft with wingspans greater than 118' exiting Rwy 31L. Twy Z clsd to acft with wingspan greater than 118'. Gnd run-up enclosure avbl 24 hrs. Terminal Gates A1, A2, A6, A7, A8, A15 & A17 use only with PPR call opns 210-413-4928. C130 and C17 type acft must park on west ramp to clear cstsms. All intl general aviation clear U.S. Cstms at North Fixed Base Operator Ramp east side, call U.S. CSTMS 210-821-6965 upon arr. SAID in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Ldg fee. Flight Notification Service (ADCUS) available.

AIRPORT MANAGER: 210-207-3444

WEATHER DATA SOURCES: ASOS (210) 939-4003 WSP.

COMMUNICATIONS: D-ATIS 118.9 (210-805-5515) **UNICOM** 122.95

RCO 122.3 (SAN ANGELO RADIO)

(R) APP CON 128.05 (091-140 SAT) 125.1 (271-359 SAT) 124.45 (360-090 SAT) 118.05 (141-270 SAT) 121.375
TOWER 119.8 **GND CON** 121.9 **CLNC DEL** 126.7

(R) DEP CON 128.05 (091-140 SAT) 125.1 (271-359 SAT) 124.45 (360-090 SAT) 118.05 (141-270 SAT)
CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS C svc ctc APP CON.

VOR TEST FACILITY (VOT) 110.4

RADIO AIDS TO NAVIGATION: NOTAM FILE SAT.

(VH) (H) VORTACW 116.8 SAT Chan 115 N29°38.64' W98°27.68' 176° 6.6 NM to fld. 1159/8E.

VOR unusable:

018°-022° byd 40 NM

028°-032° byd 40 NM

342°-347° byd 40 NM

355°-002° byd 40 NM blo 18,000'

ILS/DME 109.7 I-SAT Chan 34 Rwy 04. Class IE. Unmonitored.

ILS/DME 110.9 I-ANT Chan 46 Rwy 13R. Class IIE. DME also serves Rwy 31L.

ILS/DME 110.9 I-IZR Chan 46 Rwy 31L. Class IE. DME also serves Rwy 13R.