

SACRAMENTO MATHER (MHR)(KMHR) P (ARNG) 10 E UTC-8(-7DT) N38°33.32' W121°17.83' **SAN FRANCISCO**
 98 B TPA—See Remarks NOTAM FILE MHR **H-3B, L-2G, 3A**
RWY 04R-22L: H11301X150 (ASPH-CONC) S-160, D-280, 2S-175,
 2D-500 HIRL **IAP, AD**
RWY 04R: VASI(V4L)—GA 3.0° TCH 51'. RVR-TMR Rgt tfc.
RWY 22L: MALSR. VASI(V4L)—GA 3.0° TCH 50'. RVR-TMR
RWY 04L-22R: H6081X150 (ASPH) S-90, D-105, 2S-133, 2D-190
RWY 22R: Rgt tfc.

SERVICE: S4 **FUEL** 100LL, JET A **OX2 LGT** When ATCT clsd ACTVT
 HIRL Rwy 04R-22L; VASI Rwy 04R & 22L; MALSR Rwy 22L—CTAF.
MILITARY— **FUEL** A, A+ (avbl) 1400-0700Z†, C916-870-4704, after
 hr call out fee \$100, 20 min PN rqr.) (NC-100LL)

NOISE: Avoid noise sensitive residential areas North/East of Rwy 22L ILS
 final apch course. Turbojet nighttime noise abatement arrival and
 departure procedures in effect 0600-1500Z†. Pilot information on
 noise abatement 916-874-0359.

AIRPORT REMARKS: Attended Mon 1300-0730Z†, Tue-Fri 1100-0730Z†,
 Sat 1100-0500Z†, Sun 1300-0500Z†. Birds invof arpt. Be alert for
 large transport acft tks and Idgs and high performance military T-38
 jets. Rwy 22L calm wind rwy. TPA for piston acft 1098 (1000);
 Turbine acft 1898 (1800). Acft entering Rwy 22R tfc pattern from the
 north should expect to fly base leg extended 2 miles from rwy thld.
 Twy D limited to acft with maximum gross weight 50,000 lbs or less. Twy D1 limited to acft with wingspan more than
 69 ft. Twy D1 limited to acft with maximum gross weight 50,000 lbs or less. No fld cond NOTAMs avbl 0000-1400Z†.

AIRPORT MANAGER: 916-875-7077

WEATHER DATA SOURCES: AWOS-3PT 118.325 (916) 366-3371. SAWRS.

COMMUNICATIONS: CTAF 120.65 ATIS 118.325 UNICOM 122.95

SACRAMENTO RCO 122.4 (RANCHO MURIETA RADIO)

® **NORCAL APP/DEP CON 127.4**

TOWER 120.65 (1300-0500Z†) GND CON 121.85 CLNC DEL 121.85

CLEARANCE DELIVERY PHONE: For CD when ATCT is clsd ctc NorCal Apch at 916-361-6874.

AIRSPACE: CLASS D svc 1300-0500Z†; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE SAC.

(VH) (H) **VORTACW 115.2 SAC** Chan 99 N38°26.62' W121°33.10' 044° 13.7 NM to fld. 3/17E.

VOR unusable:

031°-041° byd 40 NM blo 5,000'
 031°-041° byd 45 NM blo 18,000'
 157°-169° byd 40 NM blo 4,500'
 157°-169° byd 56 NM blo 18,000'
 246°-251° byd 40 NM
 252°-262° byd 40 NM blo 7,000'
 252°-262° byd 65 NM
 263°-269° byd 40 NM
 353°-013° byd 40 NM blo 5,000'
 353°-013° byd 49 NM blo 5,500'
 353°-013° byd 58 NM

ILS/DME 111.35 I-MHR Chan 50(Y) Rwy 22L. Class IIE. Unmonitored when ATCT closed.

HELIPAD H1: H30X30 (ASPH)

HELIPAD H2: H100X100 (ASPH)

