

MEADVIEW

PEARCE FERRY (L25) 3 N UTC-7 N36°05.59' W114°02.80'

LAS VEGAS

2941 NOTAM FILE PRC

RWY 01-19: 2900X110 (DIRT)

RWY 01: Rgt t/c.

AIRPORT REMARKS: Unattended. Wildlife on and invof arpt. CTN: clsd rwy mkd by tires. +5 ft bushes along the east and west side of Rwy 01-19. Rwy 01-19 cntr 50 ft clear of vegetation. Rwy 01 signs 1050 ft fm rwy end 90 ft L. 550 ft stwy south of rwy cvrd with lrg rocks and vegetation. Rwy 19 signs 200 ft fm rwy end 110 ft L. Gravel apron W side of AER.

AIRPORT MANAGER: 702-659-3771

COMMUNICATIONS: CTAF 122.9

CLEARANCE DELIVERY PHONE: For CD ctc Los Angeles ARTCC at 661-575-2079.

MESA

FALCON FLD (FFZ)(KFFZ) 5 NE UTC-7 N33°27.65' W111°43.70'

PHOENIX

1394 B TPA—See Remarks NOTAM FILE FFZ

H-4J, L-5B, A

RWY 04R-22L: H5100X100 (ASPH) S-38, D-60, 2D-90 MIRL

IAP, AD

0.6% up NE

RWY 04R: REIL. PAPI(P4L)—GA 4.0° TCH 42'. Road.

RWY 22L: REIL. PAPI(P4L)—GA 4.0° TCH 49'.

RWY 04L-22R: H3799X75 (ASPH) S-12.5 MIRL 0.5% up NE

RWY 04L: REIL. PAPI(P2L)—GA 4.0° TCH 42'.

RWY 22R: REIL. PAPI(P2L)—GA 4.0° TCH 42'. Rgt t/c.

SERVICE: S4 FUEL 100LL, JET A, A1+ OX 1, 2, 3, 4 LGT ACTVT

MIRL Rwy 04L-22R; twy lgts—CTAF. When ATCT clsd MIRL Rwy 04L-22R NA; MIRL Rwy 04-22L; twy lgts preset low intst; incr intst—CTAF. PAPI Rwy 22L does not prvd obstn clnc byd 4 NM fm thr.

NOISE: Noise abatement proc in efct; quiet hr 0500-1230Z; Rwy 04L & 04R preferred; TGL 0500-1230Z NA; climb at VY until 2400 ft MSL; mntn t/c pat 3/4 mi fm rwy end.

AIRPORT REMARKS: Attended Aug 16-May 14 Fri-Sun 1230-2300Z, Aug

16-May 14 Mon-Thur 1230-0100Z, May 15-Aug 15 Fri-Sun

1200-2230, May 15-Aug 15 Mon-Thur 1200-0100. Rwy

04L-22R clsd when ATCT clsd. 150 ft x 95 ft blast pads avbl. Fuel:

A: SAF. Fixed wing and rotorcraft trng, birds and wilflife on and invof arpt. Rwy 22L right t/c when ATCT clsd or Rwy 04L-22R is clsd. Turb

psbl blw 500 ft near test site 1.5 miles N. Ctn: Heli 1 mi N; do not mistake for rwy. Twy G clsd when ATCT clsd.

TPA—2400 (1006) for light acft, 2900 (1506) for large and turbine-powered acft, 1900 (506) for rotorcraft. Rwy 04L

calm wind rwy. 2786 ft MSL unlgtd mt 5 mi E. Rising trm NE. Trng ops Rwy 04L-22R when psbl; trng ops NA

0500-1230Z. Trml apron lmdt to 45000 lb gwt single wheel or 75000 lb gwt dual wheel. NOTE: See Special

Notices—Arrival Alert.

AIRPORT MANAGER: 480-644-2450


WEATHER DATA SOURCES: ASOS (480) 641-4111 LAWRS.

COMMUNICATIONS: CTAF 124.6 ATIS 118.25 480-641-9378. UNICOM 122.95

® **PHOENIX APP/DEP CON** 120.7

TOWER 124.6 (May 15-Aug 15 1230-0400Z, Aug 16-May 14 1300-0400Z) **GND CON** 121.3

CLEARANCE DELIVERY PHONE: When ATCT clsd, for CD ctc Phoenix approach at 602-306-2565.



CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS D svc May 15–Aug 15 1230–0400Z, Aug 16–May 14 1300–0400Z; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE PRC.

PHOENIX (VH) (H) VORTACW 115.6 PXR Chan 103 N33°25.98' W111°58.21' 070° 12.3 NM to fld. 1184/12E.

VOR unusable:

000°–015° byd 33 NM blo 11,000'
 015°–034° byd 33 NM blo 10,000'
 015°–034° byd 60 NM blo 11,000'
 015°–034° byd 66 NM blo 16,000'
 035°–060° byd 40 NM blo 13,000'
 061°–067° byd 40 NM
 068°–088° byd 40 NM blo 14,000'
 068°–088° byd 60 NM
 090°–100° byd 15 NM blo 8,000'
 090°–117° byd 40 NM
 118°–141° byd 40 NM blo 9,000'
 118°–141° byd 65 NM blo 10,000'
 118°–141° byd 73 NM
 185°–190° byd 30 NM blo 8,000'
 185°–190° byd 38 NM blo 9,000'
 190°–230° byd 20 NM blo 10,000'
 231°–282° byd 40 NM
 318°–320° byd 40 NM
 323°–350° byd 40 NM blo 14,000'
 345°–000° byd 33 NM blo 10,000'
 345°–034° byd 10 NM blo 6,000'

TACAN AZIMUTH unusable:

000°–015° byd 33 NM blo 11,000'
 015°–034° byd 33 NM blo 10,000'
 090°–100° byd 15 NM blo 8,000'
 185°–190° byd 30 NM blo 8,000'
 185°–190° byd 38 NM blo 9,000'
 190°–230° byd 20 NM blo 10,000'
 345°–000° byd 33 NM blo 11,000'
 345°–034° byd 10 NM blo 6,000'
 345°–034° byd 20 NM blo 8,000'

DME unusable:

000°–015° byd 33 NM blo 11,000'
 015°–034° byd 33 NM blo 10,000'
 090°–100° byd 15 NM blo 8,000'
 185°–190° byd 30 NM blo 8,000'
 185°–190° byd 38 NM blo 9,000'
 190°–230° byd 20 NM blo 10,000'
 215°–315°
 345°–000° byd 33 NM blo 11,000'
 345°–034° byd 10 NM blo 6,000'
 345°–034° byd 20 NM blo 8,000'

VOR unusable:

345°–034° byd 20 NM blo 8,000'
 351°–359° byd 40 NM blo 12,000'

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not available at twr.

MESA GATEWAY (See PHOENIX on page 73)

MOUNT LEMMON N32°24.51' W110°44.04'
 RCO 122.4 (PRESCOTT RADIO)

PHOENIX
 L–5C
