

TOP ALTITUDE:
8000

CHARLOTTE DEP CON
124.0 307.8
D-ATIS DEP
132.1
CLNC DEL
127.15 348.6
CPDIC
GND CON
121.8 348.6 (WEST)
121.9 348.6 (EAST)
CHARLOTTE TOWER
118.1 257.8 (Rwy 18L-36R)
126.4 257.8 (Rwy 18C-36C)
133.35 257.8 (Rwy 18R-36L)

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

RALEIGH/DURHAM
RDU

TAR RIVER
TYI

FL180
*3300
078°
(71)

FL180
*2300
048°
(22)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)

FL180
*2100
077°
(13)

FL180
*1900
077°
(39)


FL180
*2100
077°
(13)

(BARMY5.BARMY) 25051
BARMY FIVE DEPARTURE (RNAV)

AL-78 (FAA)

CHARLOTTE/DOUGLAS INTL (CLT)
CHARLOTTE, NORTH CAROLINA

N



NOTE: Chart not to scale.

TAKEOFF MINIMUMS
Rwys 18L/C/R, 36C/R: Standard with minimum climb of 500' per NM to 1260.
Rwy 36L: Standard with minimum climb of 500' per NM to 1400.

NOTE: For turbo jets only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or Charlotte CLNC DEL.
NOTE: Accelerate to 250K, if unable advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

(CONTINUED ON FOLLOWING PAGE)

BARMY FIVE DEPARTURE (RNAV)
(BARMY5.BARMY) 21MAR24

CHARLOTTE, NORTH CAROLINA
CHARLOTTE/DOUGLAS INTL (CLT)