

WAAS CH 50228 W22B	APP CRS 225°	Rwy Ldg TDZE 654 Apt Elev 680
--	------------------------	---

RNAV (GPS) RWY 22L

CHICAGO O'HARE INTL (ORD)

▼



▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 22R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct CGT VORTAC and hold.

D-ATIS 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 120.75 348.0	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRs)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)	CLNC DEL 121.6	CPDLC
--------------------------	--	-------------------------------------	---	---	--------------------------	-------



1100 4000 CGT

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 73).

*LNAV only.

LAKE

2500

2500

4000

GP 3.00° TCH 55

CATEGORY	A	B	C	D
LPV DA	854/18	200 (200-½)		
LNAV/VNAV DA	1066/45	412 (400-¾)		
LNAV MDA	1120/24	466 (500-½)	1120/50	466 (500-1)
CIRCLING	1220-1	540 (600-1)	1220-1½ 540 (600-1½)	1460-2½ 780 (800-2½)