

HOUSTON, TEXAS

AL-197 (FAA)

25275

WAAS CH 70625 W17A	APP CRS 174°	Rwy Ldg 9001 TDZE 32 Apt Elev 33
--	------------------------	---

RNAV (GPS) RWY 17R
ELLINGTON (EFD)

V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP-0.3 NA. Inop table does not apply to LPV DA. For inop MALSF, increase LNAV/VNAV all Cats and LNAV Cats A and B visibility to RVR 5500 and Cats C/D/E visibility to 1½ miles. Circling NA west of Rwy 17R-35L.


MALSF



MISSED APPROACH: Climb to 3100 direct AZTIB and on track 125° to WATFO and hold.

ATIS 135.575 269.9	HOUSTON APP CON 134.45 284.0	ELLINGTON TOWER 126.05 253.5	GND CON 121.6 275.8
-----------------------	---------------------------------	---------------------------------	------------------------

RADAR REQUIRED

[illegible]

VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00°/TCH 48).				 3100 AZTIB tr 125° WATFO	
 ZORLU 2000				*LNAV only.	
GP 3.00° TCH 52					
CATEGORY	A	B	C	D	E
LPV DA	232/40		200 (200-¾)		
LNAV/ VNAV DA	363/40		331 (400-¾)		
LNAV MDA	500/40 468 (500-¾)		500/60 468 (500-1¼)		
CIRCLING	500-1	467 (500-1)	580-1½ 547 (600-1½)	640-2 607 (700-2)	700-2¼ 667 (700-2¼)

HOUSTON, TEXAS
Amdt 1C 08OCT20

29°36'N-95°10'W

ELLINGTON (EFD)
RNAV (GPS) RWY 17R

SC-5, 27 NOV 2025 to 25 DEC 2025

SC-5, 27 NOV 2025 to 25 DEC 2025