

WAAS

CH **87027**

W32A

APP CRS

322°

Rwy Idg

3510

TDZE

545

Apt Elev

556

RNAV (GPS) RWY 32

ORANGE MUNI (O.R.E.)

RNP APCH - GPS

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Rwy 32 helicopter visibility reduction below ¾ SM NA. Circling Rwy 1, 19 NA at night.

▲

Baro-VNAV and VDP NA when using Keene altimeter setting. When local altimeter setting not received, use Keene altimeter setting and increase LPV DA to 928 and all visibilities ½ SM, LNAV/VNAV DA to 1343 and all visibilities ½ SM, and all MDAs 60 feet and LNAV visibility Cat B ¼ SM, and Circling visibility Cat B ¼ SM.

MISSED APPROACH: Climb to 3500 direct CIGPA and on track 299° to WARIC and hold, continue climb-in-hold to 3500.

ASOS 135.675	BOSTON CENTER 123.75 338.2	UNICOM 122.8 (CTAF) 1
------------------------	--------------------------------------	---------------------------------



3500 CIGPA tr 299° WARIC				HUTIN Holding Pattern			
ZUGEG 2.8 NM to RW32				OMASS 2500			
RW32 1.7 NM to RW32				1600 2500			
1.7 NM 1.1 NM 2.3 NM 5 NM				142° 6000 322° 3300			
CATEGORY	A		B		C		D
LPV DA	873-1		328 (400-1)		NA		NA
LNAV/VNAV DA	1288-2		743 (800-2)		NA		NA
LNAV MDA	1240-1		695 (700-1)		NA		NA
CIRCLING	1260-1 704 (800-1)		1320-1 764 (800-1)		NA		NA