

WAAS CH 87128 W07A	APP CRS 082°	Rwy Ldg 12000 TDZE 5352 Apt Elev 5434
--	------------------------	--

RNAV (GPS) Y RWY 7

DENVER INTL (DEN)

RNP APCH - GPS.

Simultaneous approach authorized. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 54°C. LNAV procedure NA during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500, and LNAV Cat C/D visibility to RVR 5500. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5900 then climbing right turn to 10000 direct CIDMU and on track 081° to LIMEX and hold.

D-ATIS 125.6 379.9	DENVER APP CON 119.3 307.3 (N) 120.35 379.3 (S)	DENVER TOWER 128.75 273.55	GND CON 121.35 379.175 (W) 121.85 377.1 (E)
------------------------------	---	--------------------------------------	---

(IF) SARAH

8000

082°

(3.9)

ASURE

7000

(3.2)

(FAF) TAILR

SUNKE

1.1 NM to RW07

5463

RW07

MSA RW07 25 NM

10900

MISSED APCH FIX

081°

261°

7 NM

CIDMU

081°

(27.7)

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 68).

SARAH

9000

082°

ASURE

8000

7000

TAILR

SUNKE

1.1 NM to RW07

RW07

5740

GP 3.00°

TCH 55

3.9 NM

3.2 NM

4 NM

1.1 NM

5900

10000

CIDMU

tr 081°

LIMEX

CATEGORY	A	B	C	D
LPV DA	5552/18 200 (200-½)			
LNAV/VNAV DA	5626/24 274 (200-½)			
LNAV MDA	5720/24 368 (300-½)		5720/35 368 (300-¾)	

HIRL all Rwys

TDZ/CL Rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R

DENVER, COLORADO
Amdt 2 20APR23

39°52'N-104°40'W

DENVER INTL (DEN)

RNAV (GPS) Y RWY 7