

WAAS

CH **53412**

W34A

APP CRS

344°

Rwy Ldg

7455

TDZE

680

Appt Elev

710

RNAV (GPS) RWY 34

FORT WORTH MEACHAM INTL (FTW)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop MALS, increase LNAV/VNAV Cat D and LNAV Cat D visibility to 1½ mile.

MALS

MISSED APPROACH:

Climb to 3000 direct WOROD and hold.

ATIS 120.7	LONE STAR APP CON 118.1 306.95 (N) 135.975 379.9 (S)	MEACHAM TOWER 118.3 257.8	GND CON 121.9
----------------------	--	-------------------------------------	-------------------------

MISSED APCH FIX

4 NM

164°

344°

WOROD

MSA RW34 25 NM

3600

3000

WOROD

WAGMU 2.6 NM to RW34

(FAF) DOJED

2200

344°

(6)

(IF/IAF) PAXXE

164°

344°

4 NM

3000 NoPT 354° (11.9)

(IAF) CURLE

3000 NoPT (5.4)

(IAF) BARGO

ELEV 710

D

TDZE 680

91

A5

4

L1

7502 X 150

0.5% UP

35

34

344°

HIRL Rwy 16-34

MIRL Rwy 17-35

3000

WOROD

*LNAV only

1.3 NM to RW34

WAGMU 2.6 NM to RW34

DOJED

2200

344°

164°

3000

4 NM Holding Pattern

GP 3.00°

TCH 60

1.3 NM

1.3 NM

2 NM

6 NM

CATEGORY	A	B	C	D
LPV DA		880-¾	200 (200-¾)	
LNAV/VNAV DA		1091-1½	411 (400-1½)	
LNAV MDA	1160-¾	480 (500-¾)	1160-1½	480 (500-1½)
CIRCLING	1260-1 550 (600-1)	1280-1 570 (600-1)	1340-1¾ 630 (700-1¾)	1500-2½ 790 (800-2½)

FORT WORTH, TEXAS

Amtd 1 18SEP14

32°49'N-97°22'W

FORT WORTH MEACHAM INTL (FTW)

RNAV (GPS) RWY 34