

APP CRS 320°	Rwy Ldg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALS

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

MISSED APCH FIX

4 NM

139°

319°

KEADY

(IF) PNFLD
6000 210K
(RF REQD)

MSA RW32 25 NM
3100

(IF) CRCLC
6000 210K
(RF REQD)

(IF) HNKLE
5000 210K
(RF REQD)

(IF) BTTLR
2400

(IF) CUREG
200K

(IF) EVAVE
200K

(IF) BDAWG
5000
(RF REQD)

(IF) OZMOE
4500 210K

ELEV 796 D TDZE 793

3000

↑

Ir 320°

KEADY

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 73).

BTTLR

2400

GP 3.00°
TCH 53

See planview for multiple IF locations.

4.9 NM

CATEGORY

A

B

C

D

RNP 0.19 DA

1134/30

341 (400-%)

RNP 0.30 DA

1196/45

403 (400-%)

HIRL all Rwys

TDZ/CL Rwys 5L and 5R

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32