

LOC/DME I-JJM	APP CRS	Rwy Ldg	7800
110.55	350°	TDZE	479
Chan 42 (Y)		Apt Elev	501

ILS RWY 35R (SA CAT I)

LOUISVILLE MUHAMMAD ALI INTL (SDF')

Simultaneous approach authorized. Requires specific OPSPEC, MSPEC, or LOA approval.

ALSIF-2

MISSED APPROACH: Climb to 2500 then climbing left turn to 4000 on heading 350° and on IJ VORTAC R-332 to HEALS/28.3 DME/RADAR and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6
-------------------	-------------------------------------	---------------------------------	------------------------

The diagram illustrates the ILS RWY 35R approach. Key features include:

- Approach Path:** Starts at 2500 ft, descends to 4000 ft, then turns left to 350° and descends to 3000 ft. The final segment is a 3.00° glide slope to the runway.
- Navigation Aids:** Includes the I-JJM 110.55 ILS, HEALS/28.3 DME/RADAR, and various VORTAC and DME stations (R-332, R-226, R-205, R-3704 A & B, R-35R).
- Obstacles:** Several obstacles are marked with their MSL and MSLA altitudes, including IM (586/609), PARCL I-JJM (7.3), UPSCO INT I-JJM (9.9), PGSUS I-JJM (13.4), OHNNA I-JJM (17.1), and MEEKO I-JJM (21.6).
- Communication:** Frequencies for D-ATIS (118.725), APP CON (132.075/327.0), TOWER (124.2/257.8), GND CON (121.7/348.6), and UNICOM (119.1) are provided.
- Visual Aids:** The runway is shown with its 3500 ft length and 110 ft width. The runway number 35R is displayed.

ELEV 501	D	TDZE 479
----------	---	----------

This diagram shows the ILS RWY 35R approach path and associated navigation aids. Key features include:

- Approach Path:** The path starts at 2500 ft, descends to 4000 ft, then turns left to 350° and descends to 3000 ft. The final segment is a 3.00° glide slope to the runway.
- Navigation Aids:** Includes the I-JJM 110.55 ILS, HEALS/28.3 DME/RADAR, and various VORTAC and DME stations (R-332, R-226, R-205, R-3704 A & B, R-35R).
- Obstacles:** Several obstacles are marked with their MSL and MSLA altitudes, including IM (586/609), PARCL I-JJM (7.3), UPSCO INT I-JJM (9.9), PGSUS I-JJM (13.4), OHNNA I-JJM (17.1), and MEEKO I-JJM (21.6).
- Communication:** Frequencies for D-ATIS (118.725), APP CON (132.075/327.0), TOWER (124.2/257.8), GND CON (121.7/348.6), and UNICOM (119.1) are provided.

HIRL all Rwy's
TDZL/RCLS Rwy's 17L, 17R, 35L,
and 35R

This diagram shows the ILS RWY 35R approach path and associated navigation aids. Key features include:

- Approach Path:** The path starts at 2500 ft, descends to 4000 ft, then turns left to 350° and descends to 3000 ft. The final segment is a 3.00° glide slope to the runway.
- Navigation Aids:** Includes the I-JJM 110.55 ILS, HEALS/28.3 DME/RADAR, and various VORTAC and DME stations (R-332, R-226, R-205, R-3704 A & B, R-35R).
- Obstacles:** Several obstacles are marked with their MSL and MSLA altitudes, including IM (586/609), PARCL I-JJM (7.3), UPSCO INT I-JJM (9.9), PGSUS I-JJM (13.4), OHNNA I-JJM (17.1), and MEEKO I-JJM (21.6).
- Communication:** Frequencies for D-ATIS (118.725), APP CON (132.075/327.0), TOWER (124.2/257.8), GND CON (121.7/348.6), and UNICOM (119.1) are provided.

CATEGORY	A	B	C	D
S-ILS 35R	RA 162/14 150 DA 629			

SA CATEGORY I ILS- SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED

LOUISVILLE, KENTUCKY
Amdt 6 11JUL24

38°10'N-85°44'W

LOUISVILLE MUHAMMAD ALI INTL (SDF')
ILS RWY 35R (SA CAT I)