

WAAS
CH **90101**
W17B

APP CRS
170°

Rwy Ldg
TDZE **499**
Apt Elev **501**

RNAV (GPS) Y RWY 17L

LOUISVILLE MUHAMMAD ALI INTL (SDF)

RNP APCH - GPS.

Simultaneous approach authorized. Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C or above 54°C. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

MALSRR

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct IIU VORTAC and hold, continue climb-in-hold to 3000.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6
--------------------------	--	--	-------------------------------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.32/TCH 71).				
RACRR MORKK SLGRR KELEI RWY 17L				
4000 170° 3000 2500 1320				
GP 3.00° TCH 55				
3.5 NM 2.3 NM 3.7 NM 1.4 NM 1 NM				
CATEGORY	A	B	C	D
LPV DA	699/18		200 (200-½)	
LNAV/VNAV DA	909/40		410 (500-¾)	
LNAV MDA	920/24	421 (500-½)	920/40	421 (500-¾)
CIRCLING	1040-1 539 (600-1)	1140-1 639 (700-1)	1160-1¾ 659 (700-1¾)	1400-3 899 (900-3)

ELEV 501 D TDZE 499

170°

17L

7251 X 1.50

8578 X 1.50

35L

TWR

35R

35L

35R

HIRL all Rwy's

TDZL/RCLS Rwy's 17L, 17R, 35L, and 35R

LOUISVILLE, KENTUCKY

Amtd 2 11JUL24

LOUISVILLE MUHAMMAD ALI INTL (SDF)

RNAV (GPS) Y RWY 17L

38°10'N-85°44'W

SE-1, 25 DEC 2025 to 22 JAN 2026