


LOC/DME I-PLJ	APP CRS	Rwy Ldg	8002
111.35	273°	TDZE	8
Chan 50(Y)		Apt Elev	8

ILS or LOC RWY 27R

MIAMI-OPA LOCKA EXEC (OPF)

▼ ⚠ DME required. When local altimeter setting not received, use Miami Intl altimeter setting and increase all DA/MDA 20 feet and Circling Cat D visibility ¼ SM. For inop ALS, increase S-ILS 27R all Cats visibility to ¾ SM and S-LOC 27R Cats C/D visibility to 1½ SM. Rwy 27R helicopter visibility reduction below ¾ SM NA. Autopilot coupled approach NA below 700 feet.		MALS	MISSED APPROACH: Climb to 2000 heading 273° and DHP VORTAC R-335 to BRBRA/DHP 11.5 DME and hold.		
ATIS	MIAMI APP CON	OPA LOCKA TOWER ★	GND CON	CLNC DEL	GCO
125.9	128.6 306.975	134.675 (CTAF) 0	120.025	119.2	119.45

RADAR REQUIRED



ELEV 8	D	TDZE 8

2000	DHP R-335	BRBRA DHP 11.5	JOLYN INT I-PLJ 6.3 RADAR	IZROZ INT I-PLJ 11.5
hdg 273°				
1.1 NM	3.7 NM	5.2 NM		
CATEGORY	A	B	C	D
S-ILS 27R	291-¾ 283 (300-¾)			
S-LOC 27R	420-¾	412 (500-¾)	420-1	412 (500-1)
CIRCLING	540-1	532 (600-1)	620-1¾ 612 (700-1¾)	740-2¾ 732 (800-2¾)