

HURCN FOUR DEPARTURE(RNAV) Departure Routes

MIAMI DEP CON	
126.85	290.325
	D-ATIS
	133.675
	CLNC DEL
	135.35
	CPDIC
	GND CON
8L/R, 12, 26L/R)	
121.8	348.6
	(9, 27, 30)
	127.5 348.6
	MIAMI TOWER
	118.3 256.9

TOP ALTITUDE:
5000

RNAV-1 DME/DME/IRU or GPS.
RADAR required.

TAKEOFF MINIMUMS

Rwy 8I: Standard with minimum climb of 500'/NM to 520, then minimum climb of 215' to 1400.
Rwy 8R: Standard with minimum climb of 500'/NM to 520, then minimum climb of 235' to 1400.
Rwy 9: Standard with minimum climb of 500'/NM to 520, then minimum climb of 240' to 1400.
Rwy 12: Standard with minimum climb of 500'/NM to 520, then minimum climb of 230' to 1400.
Rwys 26L/R, 27, 30: Standard with minimum climb of 500'/NW to 520.

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000,
if unable, advise ATC.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SE-3, 25 DEC 2025 to 22 JAN 2026