

APP CRS
166°

Rwy Ldg
TDZE
Apt Elev
30
36

RNAV (GPS) RWY 19R
NAPA COUNTY (APC)

▼

⚠

Rwy 19R helicopter visibility reduction below ¾ SM NA.
Circling Cats A/B/C NA east of Rwy 19R and northwest of Rwy 24. Circling Cat D NA east of Rwy 19L-1R.

MISSED APPROACH: Climb to 700 then climbing right turn to 3000 direct FESAV and hold.

ATIS 124.05	OAKLAND CENTER 127.8 353.5	NAPA TOWER★ 118.70 (CTAF) 257.8	GND CON 121.7	UNICOM 122.95
-----------------------	--------------------------------------	---	-------------------------	-------------------------

MSA CUKOO 25 NM (5100)

Procedure NA for arrivals at RUMSY on V301 northeast bound.

Procedure NA for arrivals at BESSA on V195 northbound.

Procedure NA for arrivals at RAGGS on T329/V494 eastbound and V195 southbound.

Final approach course offset 20.00°.

MISSED APCH FIX

Procedure NA for arrivals at REBAS on V87 southbound and V150 southwest bound.

Key waypoints and altitudes: (IAF) RUMSY 5900, (IAF) ARRRF 5900, (IAF) BARKZ 5900, POPES 210K 3700, (IF) OIINK 3700, BAAHH 1900, (FAF) NAAYY 2900, ROOAR 1.3 NM to CUKOO 363±, (MAP) CUKOO 363±, HEHAW 6000, RRIBT 230K 6000, SNOMA 6000, BURDE 6000, WEBRR 6000, REBAS 6000.

700	3000	FESAV	VGSi and descent angles not coincident (VGSi Angle 3.25/TCH 52).		OIINK
CUKOO		ROOAR 1.3 NM to CUKOO	166°	1900	3700
0.5		1.3 NM	3.1 NM	3.2 NM	3.4 NM
CATEGORY	A	B	C	D	
LNAV MDA	680-1	650 (700-1)	680-1⅞	650 (700-1⅞)	
CIRCLING	680-1	644 (700-1)	1280-3 1244 (1300-3)	1300-3 1264 (1300-3)	

ELEV 36 TDZE 30

166°

0.3% UP 5920 X 1.30

0.4% UP 2510 X 1.75

0.4% UP 5008 X 1.50

IL TWR

REIL Rwy 6

MIRL Rwy 6-24 and 1L-19R

NAPA, CALIFORNIA

Orig 05SEP24

38°13'N-122°17'W

NAPA COUNTY (APC)

RNAV (GPS) RWY 19R