

|                                        |                        |                                                   |
|----------------------------------------|------------------------|---------------------------------------------------|
| WAAS<br>CH <b>78019</b><br><b>W22A</b> | APP CRS<br><b>221°</b> | Rwy Ldg<br>TDZE <b>270</b><br>Apt Elev <b>288</b> |
|----------------------------------------|------------------------|---------------------------------------------------|

RNAV (GPS) RWY 22

AUBURN/LEWISTON MUNI (LEW)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                          |                                                       |                                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------------------------------------------|---------------------------------|
| RNP APCH.<br><div><div>▼</div><div>⚠</div></div> <div>Procedure NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 22 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Augusta altimeter setting: increase LPV all Cats DA to 617 feet and all Cats visibility ½ SM; LNAV/VNAV all Cats DA to 938 feet and all Cats visibility ½ SM; increase all MDA 80 feet and LNAV Cat C/D visibility ½ SM. Baro-VNAV NA when using Augusta altimeter setting.</div> |                                          | MISSED APPROACH: Climb to 3100 direct AUBIN and hold. |                                 |
| AWOS-3PT<br><b>118.025</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | PORTLAND APP CON ★<br><b>125.5 353.9</b> | CLNC DEL<br><b>124.05</b>                             | UNICOM<br><b>122.8 (CTAF) 0</b> |

