

WAAS CH 86902 W24A	APP CRS 241°	Rwy Idg TDZE 16 Apt Elev 18	5000
--	------------------------	---	-------------

RNAV (GPS) RWY 24

BOWERMAN FLD (HQM)

▼


▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 43°C (109°F). When local altimeter setting not received, procedure NA. Circling NA northwest of Rwy 6-24. DME/DME RNP-0.3 NA. For inoperative MALSR, increase LPV Cat C visibility to ¾ mile and LNAV Cat C visibility to 2½ miles.

MALSR

MISSED APPROACH:
Climb to 2600 direct ZUNAD and hold.

ASOS 135.775	SEATTLE CENTER 128.3 269.0	UNICOM 122.7 (CTAF) 0
------------------------	--------------------------------------	---------------------------------



ELEV 18

TDZE 16

REIL Rwy 6 0

HIRL Rwy 6-24 0

2600 ZUNAD				
* LNAV Only.				
RW24 2.3 NM to RW24				
FODUL 2.3 NM to RW24				
NEYDI 2100				
LAMMB 2900				
GP 3.50° TCH 55				
CATEGORY	A	B	C	D
LPV DA	226-½	210 (300-½)	286-½ 270 (300-½)	NA
LNAV/VNAV DA	676-1½		660 (700-1½)	
LNAV MDA	800-½ 784 (800-½)	800-¾ 784 (800-¾)	800-1¾ 784 (800-1¾)	NA
CIRCLING	800-1 782 (800-1)	800-1¼ 782 (800-1¼)	800-2¼ 782 (800-2¼)	NA