

LOC/DME I-JDL	APP CRS	Rwy Ldg	8457
109.9	071°	TDZE	25
Chan 36		Apt Elev	25

LDA X RWY 8

JUNEAU INTL (JNU)(PAJN)

ADF required.

⚠

1°C

↻

Circling to Rwy 26 NA at night. Circling NA north of Rwy 8-26. Rwy 8 helicopter visibility reduction below 1 SM NA. Inop table does not apply. When Juneau altimeter setting not received, procedure NA. CAUTION: Any go-around after passing MAP will not provide standard obstruction clearance. Circling Cat A night visibility minimum 5 SM, Circling Cat B, C, D night visibility minimum 10 SM. Straight-in Rwy 8 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MALSF

⚠

↻

MISSED APPROACH: Immediate climbing right turn to 5600 on heading 310° and on CGL NDB bearing 251° to intercept SSR VORTAC R-027 direct SSR VORTAC or EEF NDB and hold.

ATIS	ANCHORAGE CENTER	JUNEAU TOWER *	GND CON	CLNC DEL	JUNEAU RADIO	UNICOM
135.2	133.9	118.7 (CTAF) 0 278.3	121.9	121.9	122.2	122.95

LYNNS I-JDL 14		5600	CGL 251°	SSR R-027	EEF
Remain within 10 NM		hdg 310°			
DIBOL I-JDL 18		BARLO I-JDL 8	CGL NDB I-JDL 2		
6300		6300	5600	3700	
Use I-JDL DME when on LDA course.		4 NM	6 NM	6 NM	3.2 NM
CATEGORY	A	B	C	D	
S-LDA 8	3200-4 3175 (3200-4)			NA	
CIRCLING	3200-4 3175 (3200-4)			3340-4 3315 (3400-4)	3700-4 3675 (3700-4)

JUNEAU, ALASKA

Amdt 12E 15JUN23

58°21'N-134°35'W

JUNEAU INTL (JNU)(PAJN)

LDA X RWY 8