

LOC I-GRR 109.7	APP CRS 267°	Rwy Ldg 10001 TDZE 790 Apt Elev 794
---------------------------	------------------------	--

ILS or LOC RWY 26L

GERALD R FORD INTL (GRR)

▼


▲

For inop ALS increase S-LOC 26L Cat C/D visibility to 1½ SM.
* RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 direct VIO VOR/DME and hold, continue climb in hold to 3000.

ATIS 118.725	GREAT LAKES APP CON★ 128.4 257.6	GRAND RAPIDS TOWER★ 135.65 (CTAF) 0 339.8	GND CON 121.8	UNICOM 122.95
------------------------	--	---	-------------------------	-------------------------



ELEV 794 TDZE 790

MIRL Rwy 8L-26R
REIL Rwys 8L, 17 and 26R
HIRL Rwys 8R-26L and 17-35

FAF to MAP 5.7 NM

Knots	60	90	120	150	180
Min:Sec	5:42	3:48	2:51	2:17	1:54

1300	3000	VIO				
VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 73).						
CATEGORY	A		B		C	D
S-ILS 26L *	990/24					200 (200-½)
S-LOC 26L	1360/24	570 (600-½)		1360-1¼		570 (600-1¼)
CIRCLING	1360-1	566 (600-1)		1360-1½ 566 (600-½)		1380-2 586 (600-2)
GLGHR INT MINIMUMS (DUAL VOR RECEIVERS REQUIRED)						
S-LOC 26L	1120/24	330 (400-½)		1120/26		330 (400-½)
CIRCLING	1260-1	466 (500-1)		1340-1½ 546 (600-½)		1380-2 586 (600-2)