



WAAS CH 69623 W27A	APP CRS 270°	Rwy Ldg TDZE 239 Apt Elev 246
--	------------------------	---

RNAV (GPS) RWY 27
WINDHAM (IJD)

▼ Procedure NA at night. DME/DME RNP-0.3 NA. Rwy 27 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Windsor Locks altimeter setting and increase all MDA 80 feet, increase LP and LNAV Cat B and Circling Cats A/B visibility ¼ SM, increase LP, LNAV and Circling Cat C visibility ½ SM. ▲	MISSED APPROACH: Climbing left turn to 2600 direct ORW VOR/DME and hold.
---	---

ASOS 133.675	BRADLEY APP CON 127.8 269.325	CLNC DEL 128.6	UNICOM 122.975 (CTAF) 0
------------------------	---	--------------------------	-----------------------------------



2600	ORW	Visual Segment - Obstacles.	HHOTT	4 NM Holding Pattern
HUVUX 3.1 NM to RW27	LINKS	2200	090° 270°	2500
RW27	1260	3.1 NM 2.9 NM 6 NM		
CATEGORY	A	B	C	D
LP MDA	940-1 701 (700-1)		940-2 701 (700-2)	NA
LNAV MDA	960-1 721 (800-1)		960-2 721 (800-2)	NA
CIRCLING	980-1 734 (800-1)		1120-2½ 874 (900-2½)	NA

NE-1, 25 DEC 2025 to 22 JAN 2026

NE-1, 25 DEC 2025 to 22 JAN 2026