

APP CRS	Rwy Ldg	9000
267°	TDZE	96
	Apt Elev	96

RNAV (RNP) Y RWY 26R
GEORGE BUSH INTCNL/HOUSTON (IAH)

⚠ For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cnts visibility to RVR 5000 and increase RNP 0.15 all Cnts visibility to 1½ SM. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALS-F-2

A

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct PEPBI and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 120.725 290.2	GND CON 118.575
------------------	--	--------------------------------	--------------------

4 NM

3.5°

PEPBI

RADAR REQUIRED

ELEV	96	TDZE	96
267° 9000 X 1.50 9402 X 1.50 10000 X 1.50 1201 X 1.50 1000 X 1.50 331 33R TWR			
TDZ/CL Rwy 8R, 8L, 15R, 26R, 26L, 27 and 33L HIRL all Rwy			

600	3000	PEPBI	See planview for multiple IF locations.	
↑	↪	△		
RWY 26R SOOPR OWELL 2000 267° 2600 2000 5.8 NM 2.6 NM GP 3.00° TCH 59				
CATEGORY	A	B	C	D
RNP 0.11 DA		429/40	333 (400-¾)	
RNP 0.15 DA		496/45	400 (400-⅞)	
RNP 0.30 DA		554/50	458 (500-1½)	

AUTHORIZATION REQUIRED