

WAAS
CH **72926**
W09A

APP CRS
087°

Rwy Ldg **10000**
TDZE **91**
Apt Elev **96**

RNAV (GPS) Z RWY 9

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C (27°F) or above 54°C (130°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to 1½ mile, and LNAV Cat C/D/E visibility to 1¾ mile. Simultaneous approach authorized with Rwy 8L/R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 580 then climbing right turn to 3000 direct JEBOX and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 E 124.35 316.15 W	HOUSTON TOWER 135.15 290.2	GND CON 118.575
-------------------------	--	--------------------------------------	---------------------------

RADAR REQUIRED

URANG

CHILT

MEDIC

DOHNN

SAYNO

HYWAY

RWY 09

5000

5000

4000

4000

3000

2000

2000

1.3

GP 3.00°

TCH 50

5 NM

4.3 NM

3.8 NM

3.9 NM

4.7 NM

4.5 NM

1.3

580

3000

JEBOX

*LNAV only.

*1.3 NM to RWY 09

ELEV 96

TDZE 91

9000 X 1.50

206

201

10000 X 1.50

27

33L

33R

TDZ/CL Rwy 8R, 8L, 15R, 26R, 26L, 27 and 33L

HIRL all Rwy

HOUSTON, TEXAS

Amtd 5B 07DEC17

GEORGE BUSH INTCNL/HOUSTON (IAH)

29°59'N-95°20'W

RNAV (GPS) Z RWY 9