

WAAS CH 82707 W30B	APP CRS 295°	Rwy Ldg TDZE 5599 Apt Elev 5673
--	------------------------	---

RNAV (GPS) RWY 30R
ROCKY MOUNTAIN METRO (BJC)


NA

Baro-VNAV and VDP NA when using Denver Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C (-14°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Denver Intl altimeter setting and increase all DA 82 feet and all MDA 100 feet, increase LNAV/VNAV all Cats, LNAV Cat C/D and Circling Cat C visibility ¼ mile. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to 1 ½ mile and LNAV Cat C/D visibility to 1 mile. For inoperative MALSR, when using Denver Intl altimeter setting, increase LPV all Cats visibility to 1 mile, LNAV/VNAV all Cats visibility to 1 ½ mile and LNAV Cat A/B visibility to 1 mile and Cat C/D visibility to 1 ¾ mile.


MALSR

MISSED APPROACH: Climb to 6300 then climbing right turn to 10300 direct HYGEM and hold, continue climb-in-hold to 10300.

ATIS 126.25	DENVER APP CON 125.12 263.02	METRO TOWER ★ 118.6 (CTAF) 0 233.7	GND CON 121.7
-----------------------	--	--	-------------------------



ELEV 5673	D	TDZE 5599
-----------	----------	-----------



6300	10300	HYGEM	ALUKE	BAAWL
			VOGFA 1.9 NM to RW30R	
*LNAV only.				
		1 NM to RW30R	295°	7000
		6220*	7000	GP 3.00° TCH 52
		1 NM	0.9	2.4 NM
		4 NM		
CATEGORY	A	B	C	D
LPV DA	5799-½		200 (200-½)	
LNAV/VNAV DA	5900-⅝		301 (300-⅝)	
LNAV MDA	5940-½	341 (300-½)	5940-⅝	341 (300-⅝)
CIRCLING	6180-1 507 (600-1)	6240-1 567 (600-1)	6360-2 687 (700-2)	6860-3 1187 (1200-3)