

LOC I-IVI
111.1

APP CRS
058°

Rwy Idg
TDZE
Apt Elev
5500
2402
2419

ILS or LOC RWY 6R

RYAN FLD (RYN)

ADF required.

NA

Circling NA for Cat D north of Rwy 24R and east of Rwy 15.


MISSED APPROACH: Climb to 3000, then climbing right turn to 5000 via direct RBJ NDB and 305° bearing RBJ to DRIBB INT and hold.

ATIS
133.35

TUCSON APP CON
128.5 273.6

RYAN TOWER ★
125.8 (CTAF) **0**

GND CON
118.2



ELEV 2419 TDZE 2402

MRL Rwy 6L-24R
REIL Rwys 6R and 6L
MRL Rwys 6R-24L and 15-33

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

One Minute Holding Pattern

DRIBB INT

NIKEE OM

5000

305°

125°

058°

4262

4300

GS 3.00° TCH 50

4.7 NM

5.6 NM

CATEGORY	A	B	C	D
S-ILS 6R	2652-1 250 (300-1)			
S-LOC 6R	2900-1	498 (500-1)	2900-1¼ 498 (500-1¼)	2900-1½ 498 (500-1½)
CIRCLING	2960-1	541 (600-1)	3040-1¾ 621 (700-1¾)	3320-3 901 (1000-3)