

RNP APCH-GPS.

▼

Rwy 18 helicopter visibility reduction below $\frac{3}{4}$ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.

MISSED APPROACH: Climb to 3100 direct USXEL and hold.

AWOS-3PT 118.525	GRAY APP CON 120.075 323.15	UNICOM 122.7 (CTAF) 0
----------------------------	---------------------------------------	---------------------------------

MSA RW 18 25 NM

3400

Procedure NA for arrivals at BUILT on V161 southbound.

1760

BUILT

3600 033° (13.6)

1386

1656

KUYNU 2.2 NM to RW18

1528

2500 182° (6.9)

(F) FENIV

3600 NoPT 272° (5.3)

(IF/IAF) ULIGY

(IAF) MEZXI

3600 282° (22.1)

SONET

Procedure NA for arrivals at SONET on V358 northeast bound.

MISSED APCH FIX

USXEL

002° 182° 4 NM

ELEV 1305	TDZE 1305
-----------	-----------

182° to RW18

81

5012 x 75

36

MIRL Rwy 18-36 0

3100	USXEL	4 NM Holding Pattern
------	-------	----------------------

*LNAV only.

*0.9 NM to RW18

KUYNU 2.2 NM to RW18

FENIV 2500

ULIGY

002° 182° 6000 3600

GP 3.00° TCH 40

0.9	1.3 NM	1.4 NM	6.9 NM
-----	--------	--------	--------

CATEGORY	A	B	C	D
LPV DA	1555-1	250 (300-1)		NA
LNAV/VNAV DA	1555-1	250 (300-1)		NA
LNAV MDA	1640-1	335 (400-1)		NA
CIRCLING	1680-1 375 (400-1)	1840-1 535 (600-1)	1960-1¾ 655 (700-1¾)	NA

HAMILTON, TEXAS

Amdt 1E 16JUN22

31°40'N-98°09'W

HAMILTON MUNI (MNZ)

RNAV (GPS) RWY 18