

LOC I-PBV 110.1	APP CRS 111°	Rwy Idg 4982 TDZE 128 Apt Elev 128
---------------------------	------------------------	---

ILS or LOC RWY 11

ST GEORGE (PBV) (PAPB)

⚠

DME from SRI NDB/DME. Simultaneous reception of I-PBV and SRI DME required. Circling NA north of Rwy 11-29. ADF and DME required. Inop table does not apply to S-LOC 11 Cats A and B and S-ILS 11 all Cats.

MALSF

MISSED APPROACH: Climb to 3200 on SRI NDB/DME bearing 110° to LIJFY/SRI 7.7 DME and hold, continue climb-in-hold to 3200.

ASOS 135.45	ANCHORAGE CENTER 119.1 339.8	CTAF 122.8
-----------------------	--	----------------------

ELEV 128	TDZE 128
----------	----------

111° 5 NM from FAF

4982 X 1.50

REIL Rwy 29

HIRL Rwy 11-29

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

ADF and DME REQUIRED

Remain within 10 NM

APOTE SRI 6

3000

291°

2100

111°

2100

WVOG SRI 3.3

3200

LIJFY SRI 7.7

SRI 110°

* LOC only

* SRI 2.7

SRI 1

SRI NDB/DME

* 1060

2.7 NM

0.6 NM

1.7 NM

GS 3.60°

TCH 56

CATEGORY	A	B	C	D
S-ILS 11	428-1 300 (300-1)			NA
S-LOC 11	840-1	712 (800-1)	840-1¾ 712 (800-1¾)	NA
CIRCLING	840-1 712 (800-1)	980-1¼ 852 (900-1¼)	980-2½ 852 (900-2½)	NA

ST GEORGE, ALASKA
Amdt 1 13SEP18

56°35'N-169°40'W

ST GEORGE (PBV) (PAPB)
ILS or LOC RWY 11