VASHON MUNI (2S1) 1 NW UTC–8(–7DT) N47°27.52´ W122°28.62´ **SEATTLE**
316 TPA—1299(983) NOTAM FILE SEA
RWY 17–35: 2001X60 (TURF) LIRL(NSTD) 0.4% up N
RWY 17: Trees. Rgt tfc.
RWY 35: Trees.
NOISE: Noise abatement procs in efct. Ctc amgr 202–641–2050.
AIRPORT REMARKS: Unattended. Ocnl large wild animals on arpt. Rwy 17–35 soft when wet. Hangars 90´ east and west of cntrln. Hill 5–10 ft W of rwy edge the full len. Touch and go ldgs not recommended. Turbulence possible at north end of Rwy 17–35 with strong crosswinds. Helicopter parking area rstd to Medevac ops. Rcmd clg for fld conds 202–641–2050. Ngt ops only for pilots familiar with arpt close in obst, all quadrants. Rwy 17–35 NSTD LIRL, thld lgts 360° green. Gate combination 1168.
AIRPORT MANAGER: 202-641-2050
COMMUNICATIONS: CTAF 122.9
CLEARANCE DELIVERY PHONE: For CD ctc Seattle Apch at 206-214-4723.

• • • • • • • • • • • • • • • • • •

HELIPAD H1: 98X98 (TURF) RWY LGTS(NSTD)
HELIPORT REMARKS: Helipad H1 G perimeter lgts. Helipad H1 for medivac emerg svcs only. Helipad H1 NSTD rwy lgts.

WALLA WALLA RGNL (ALW)(KALW) 3 NE UTC–8(–7DT) N46°05.55´ W118°17.04´ **SEATTLE**
1194 B Class I, ARFF Index A NOTAM FILE ALW **H–1C, L–13A**
RWY 02–20: H6527X150 (CONC–GRVD) S–84, D–107, 2D–164 PCR 340 F/D/X/T HIRL 0.6% up NE **IAP, AD**
RWY 02: REIL. PAPI(P4L)—GA 3.0° TCH 45´. RVR–R
RWY 20: MALSR. PAPI(P4L)—GA 3.0° TCH 50´. RVR–T
RUNWAY DECLARED DISTANCE INFORMATION
RWY 02: TORA–6527 TODA–6527 ASDA–6527 LDA–6527
RWY 20: TORA–6527 TODA–6527 ASDA–6527 LDA–6527
SERVICE: S4 **FUEL** 100LL, JET A **OX** 2 **LGT** When ATCT clsd ACTVT MALSR Rwy 20, REIL Rwy 02 and HIRL Rwy 02–20—CTAF.
AIRPORT REMARKS: Attended 1600–0200Z‡. Self svc credit card fueling facility lctd 600 ft north of ATCT. 24 hr fuel svc call 509–540–1081. Sfc conds unmon 0800–1100Z‡. ARFF svcs avbl dur scheduled air carrier opr. Clsd to unscheduled air carrier ops with more than 30 pax seats exc PPR call amgr 509–525–3100. Portion of corner at Twy A and Twy A1 not visible by tower. Ctc amgr 509–525–3100 for arngmt for ramp prkg 175,000 lbs mtow. Twy A, A1, A2, A3, A4, A5 open to air carriers.
AIRPORT MANAGER: 509-525-3100
WEATHER DATA SOURCES: ASOS 135.875 (509) 525–3014.
COMMUNICATIONS: CTAF 118.5 **UNICOM** 122.95
RCO 122.3 (SEATTLE RADIO)
Ⓡ **SPOKANE APP/DEP CON** 133.15 (1400–0600Z‡)
Ⓡ **SEATTLE CENTER** 132.6 (0600–1400Z‡)
TOWER 118.5 (1400–0230Z‡) **GND CON** 121.6
CLEARANCE DELIVERY PHONE: For CD when ALW ATC is clsd ctc Spokane Apch at 509-742-2525. When Apch clsd ctc Seattle ARTCC at 253-351-3694
AIRSPACE: CLASS D svc 1400–0230Z‡; other times CLASS E.
RADIO AIDS TO NAVIGATION: NOTAM FILE ALW.
(VL) (DH) VORW/DME 116.4 ALW Chan 111 N46°05.22´ W118°17.55´ at fld. 1150/14E.
VOR unusable:
016°–071° byd 31 NM blo 12,500´
032°–042° byd 40 NM blo 12,500´
032°–042° byd 62 NM
042°–169° byd 40 NM
071°–101° byd 20 NM blo 14,500´
101°–146° byd 20 NM blo 13,500´
256°–285° byd 40 NM
286°–296° byd 40 NM blo 4,000´
286°–296° byd 50 NM
291°–302° byd 40 NM
309°–319° byd 40 NM blo 4,000´
309°–319° byd 85 NM
320°–031° byd 40 NM
DME unusable:
071°–101° byd 20 NM blo 14,500´
116°–071° byd 31 NM blo 12,500´
146°–151° byd 20 NM blo 11,500´
TRINA NDB (LOMW) 353 AL N46°10.53´ W118°11.78´ 202° 6.2 NM to fld. 1443/14E.
ILS 111.7 I–ALW Rwy 20. Class IE. LOM TRINA NDB.
COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.