

SALT LAKE CITY

4536 B NOTAM FILE RNO

H-3C, L-9B, 11B

RWY 04-22: H7300X150 (ASPH) S-30, D-125 PCR 63 F/C/W/T MRL

IAP, AD

RWY 04: REIL. PAPI(P4R)—GA 3.2° TCH 50'.

RWY 22: REIL. PAPI(P4L)—GA 3.0° TCH 51'.

RWY 13-31: H7299X100 (ASPH) S-30, D-104 PCR 63 F/C/W/T MRL

SERVICE: S4 FUEL 100LL, JET A LGT ACTVT REIL Rwy 04 and Rwy 22; PAPI Rwy 04 and Rwy 22; MIRL Rwy 04—22 and Rwy 13—31; peri lgts H1—CTAF.

AIRPORT REMARKS: Attended Oct-May 1500-0100Z†, Jun-Sep 1500-0200Z†. After hrs call 775-635-2245. Rwy 13-31 pci 54 L and T alligator patching, bone cracking, weeds growing thru cracks. (E81) Edge reflectors on twys and ramp. Rwy 04 and Rwy 22 rwy nrs faded. Rwy 13 and Rwy 31 thr markings faded.

AIRPORT MANAGER: 775-455-6860

WEATHER DATA SOURCES: AWOS-3 119.45 (775) 635-8419.

COMMUNICATIONS: CTAF/UNICOM 122.8

RCO 122.4 (RENO RADIO)

① SALT LAKE CENTER APP/DEP CON 132.25

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Salt Lake ARTCC at 801-320-2568.

AIRSPACE: CLASS E.

RADIO AIDS TO NAVIGATION: NOTAM FILE RNO.

(VH) (H) VORTACW 112.2 BAM Chan 59 N40°34.14' W116°55.34' 038° 2.8 NM to fld. 4544/13E.

VOR unusable:

037°–054° byd 40 NM blo 11,000'

037°–054° byd 55 NM

055°–065° byd 30 NM blo 12,000'

056°–075° byd 40 NM

120°–170° byd 15 NM blo 12,000'

242°–273° byd 40 NM

260°–295° byd 15 NM blo 12,000'

290°–297° byd 40 NM

TACAN AZIMUTH unusable:

055°–065° byd 30 NM blo 12,000'

120°–170° byd 15 NM blo 12,000'

260°–295° byd 15 NM blo 12,000'

DME unusable:

055°–065° byd 30 NM blo 12,000'

120°–170° byd 15 NM blo 12,000'

251°–260° byd 34 NM blo 14,000'

260°–295° byd 15 NM blo 12,000'

HELIPAD H1: H60X60 (CONC) PERIMETER LGTS

PERIMETER LGTS

HELIPAD H2: H60X60 (CONC) PERIMETER LGTS

PERIMETER LGTS

HELIPORT REMARKS: Rwy H1 perimeter lgts. ACTVT PAPI Rwy 22; MIRL Rwy 04-22 and 13-31; perimeter lgts H1—CTAF.

H1 and H2 mrkd with black outline partially vsb. W interior gone.