

TOP ALTITUDE:
RWYS 13L/R: 8000
RWYS 31L/R: 3000

LONE STAR DEP CON
125.125 353.95
D-ATIS
120.15
CLNC DEL
127.9
CPDLC
GND CON
121.75 348.6
LOVE TOWER
123.7 239.3

HUDAD

HUIZE

HRPER

BRHMA

KATZZ

MUTEE

DBLSS

PGLET

TYGGR

DRSET

CIKAN

ALIAN

RUFFS

FUMED

LYNDE

RBBIT

KKITY

CURLO

WSTEX

DOSXX

WSTEX

WSTEX

WSTEX

WSTEX

KKITY FIVE DEPARTURE (RNAV)

(KKITY5.KKITY) 05DEC19

AL-106 (FAA)

DALLAS LOVE FLD (DAL)
DALLAS, TEXAS

TAKEOFF MINIMUMS
RWys 13L/R: Standard with minimum climb of 500' per NM to 1200.
RWys 31L/R: Standard with minimum climb of 500' per NM to 1000.

- NOTE: RADAR required.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.
- NOTE: For use by turbojet aircraft only.
- NOTE: RNAV-capable props: File and expect the SWABR RNAV SID.
- NOTE: ALIAN Transition: ATC assigned only.
- NOTE: BRHMA Transition: For aircraft inbound to Lubbock terminal area.
- NOTE: Use WORTH DEPARTURE during the period 2100-0600 local time in lieu of the KKITY DEPARTURE.
- NOTE: WSTEX Transition: For aircraft inbound to Abilene and San Angelo terminal area airports only.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.