

WAAS
CH **60901**
W09B

APP CRS
094°

Rwy Ldg **10181**
TDZE **32**
Apt Elev **33**

RNAV (GPS) RWY 9R

MELBOURNE ORLANDO INTL (MLB)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C.

MALSR

A5

MISSED APPROACH: Climb to 2000 direct ZUVOM and hold.

ATIS 132.55	ORLANDO APP CON 126.025 281.425	MELBOURNE TOWER ★ 118.2(CTAF) 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	---	---	-------------------------	-------------------------

Procedure NA for arrivals at PRESK on V159-537 northwest bound.

Key features of the chart include:

- Waypoints:** SUZEN, FIFMU (IAF), SUROY (IF/IAF), JINBA (FAF), NAJBE (IAF), WIXED.
- Altitudes:** 3000, 2000, 1600, 6000, 2000, 3000.
- Distances:** 13.1 (10), 6.8, 1.8, 4 NM, 6 NM, 3.6 NM, 1.1 NM.
- Angles:** 131°, 131°, 180°, 094°, 274°, 321°.
- Missed Approach:** Climb to 2000 direct ZUVOM and hold.
- Obstacles:** W-497B, TWR, 10181 X 150, 6000 X 150.
- MSA:** MSA RW09R 25 NM, 3000.

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 83).

SUROY

JINBA

RW09R

6000

2000

1600

2000

GP 3.00°

TCH 55

274°

094°

094°

274°

6 NM

3.6 NM

1.1 NM

1.1 NM to RW09R

2000

ZUVOM

094°

6000 X 150

10181 X 150

TWR

6000 X 150

271

CATEGORY	A	B	C	D
LPV DA	232/18 200 (200-½)			
LNAV/VNAV DA	427/35 395 (400-⅝)			
LNAV MDA	480/24 448 (500-½)	480/45 448 (500-⅞)		
CIRCLING	500-1 467 (500-1)	560-1 527 (600-1)	680-1¾ 647 (700-1¾)	880-2¾ 847 (900-2¾)

REIL Rwy 27L

HIRL Rwy 9R-27L

MIRL Rws 5-23 and 9L-27R

TDZ/CL Rwy 9R

MELBOURNE, FLORIDA

Amtd 2 20FEB25

28°06'N-80°39'W

MELBOURNE ORLANDO INTL (MLB)

RNAV (GPS) RWY 9R