



APP CRS	Rwy Ldg	12000
344°	TDZE	4229
	Apt Elev	4231

RNAV (RNP) Z RWY 34L
SALT LAKE CITY INTL (SLC)

RNP AR APCH - GPS. Authorization required. From PEFNO: RF.	ALSF-2	MISSED APPROACH: Climb to 4800 then climbing left turn to 8100 direct STACO and hold.
▼ For uncompensated Baro-VNAV systems, procedure NA below -10°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.10, RNP 0.20 visibility all Cats to RVR 4500, RNP 0.30 visibility all Cats to RVR 6000.		*Missed approach requires minimum climb of 250 feet per NM to 4700.

D-ATIS	SALT LAKE CITY APP CON	SALT LAKE CITY TOWER	GND CON	CLNC DEL	CPDLC
124.75 125.625	125.7 284.6	132.65 336.4	123.775 348.6	127.3 379.975	



4800

8100

STACO

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

HEPSO

7900

FLAG

6100

344°

6100

See planview for multiple IF locations.

RW34L

GP 3.00°

TCH 55

5.7 NM

5.8 NM

CATEGORY	A	B	C	D
RNP 0.10 DA*	4490/24 261 (300-½)			
RNP 0.20 DA	4530/24 301 (300-½)			
RNP 0.30 DA	4643/40 414 (500-¾)			

AUTHORIZATION REQUIRED

SW-4, 22 JAN 2026 to 19 FEB 2026

SW-4, 22 JAN 2026 to 19 FEB 2026