

WAAS CH 65806 W23A	APP CRS 230°	Rwy Ldg TDZE 262 Apt Elev 262
--	------------------------	---

RNAV (GPS) RWY 23

JONESBORO MUNI (JBR)

RNP APCH.

▼

⚠

Circling NA northwest of Rwy 5-23. Circling Rwy 31 NA at night. Baro-VNAV and VDP NA when using Walnut Ridge altimeter setting. Rwy 23 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. For inop ALS, increase LPV Cat A/B visibility to ¾ SM. Inop table does not apply to LNAV/VNAV. For inop ALS when using Walnut Ridge altimeter setting, increase LPV Cat A/B visibility to 1 SM. When using Walnut Ridge altimeter setting, inop table does not apply to LNAV/VNAV. When local altimeter setting not received, use Walnut Ridge altimeter setting: increase LPV DA to 600 feet, LNAV/VNAV DA to 630 feet and all visibilities ¾ SM; increase all MDAs 60 feet and LNAV Cat C/D and Circling Cat C visibility ¼ SM.

ODALS

MISSED APPROACH:
Climb to 2300 direct YIGUY and hold.

ASOS 118.525	MEMPHIS CENTER 120.075 289.4	UNICOM 123.0 (CTAF) ①
------------------------	--	---------------------------------

ELEV 262		TDZE 262		
2300 YIGUY				
*LNAV only. 1.2 NM to RW23 1.7 NM 3 NM 7 NM JERLO 2.9 NM to RW23 LNDRY 2200 PUKKO 4 NM Holding Pattern 2300 2200 2200 1220 230° 050° 230° GP 3.00° TCH 53				
CATEGORY	A	B	C	D
LPV DA	546-¾ 284 (300-¾)			
LNAV/VNAV DA	576-7/8 314 (400-7/8)			
LNAV MDA	680-¾ 418 (500-¾)		680-1 418 (500-1)	
CIRCLING	740-1 478 (500-1)		820-1½ 1080-2¾ 558 (600-1½) 818 (900-2¾)	
MIRL Rwy 5-23 and 13-31 ①				

JONESBORO, ARKANSAS
Amdt 1C 25MAR21

35°50'N-90°39'W

JONESBORO MUNI (JBR)

RNAV (GPS) RWY 23