


ILS or LOC Y RWY 15L

LOC I-TRT 109.9	APCH CRS 145°	Rwy Idg TDZE Arpt Elev 8351 742 761	[USAF]	RANDOLPH AFB (KRND)
---------------------------	-------------------------	---	--------	---------------------

RADAR or DME required		ALS-F1 	MISSED APPROACH: Climb to 1500, then climbing left turn heading 024° to 3000. Intercept DHK TACAN R-054 to WIMVI and hold.
* When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE to 1 1/2 miles.			
** Circling not authorized SW of Rwy 15L-33R.			

ATIS ★	SAN ANTONIO APP CON	TOWER ★	GND CON	CLNC DEL (RWY 15L-33R)	HANGOVER ATIS ★	HANGOVER TOWER ★	HANGOVER GND CON
290.525	128.05 318.1	128.25 294.7	119.65 275.8	338.35	327.8	120.5 291.1	124.75 353.75





Simultaneous approaches authorized with Rwy 15L and 15R.

SC-3, 19 FEB 2026 to 19 MAR 2026

SC-3, 19 FEB 2026 to 19 MAR 2026

EMERG SAFE ALT 100 NM 4100	ELEV 761	TDZE 742
----------------------------	----------	----------



CATEGORY	A	B	C	D	E
S-ILS 15L	942/40		200	(200-3/4)	
S-LOC 15L *	1260/40	518 (500-3/4)	1260-1 1/4	518 (500-1 1/4)	
CIRCLING **	1260-1	499 (500-1)	1260-1 1/2 499 (500-1 1/2)	1900-3	1139 (1200-3)

HIRL all rwys ALS Rwy 15L nstd len 2100'					
FAF to MAP 3.7 NM					
Knots	60	90	120	150	180
Min:Sec	3:42	2:28	1:51	1:29	1:14

ILS or LOC Y RWY 15L