
D-ATIS
132.65
CLNC DEL
128.25
CPDLC
GND CON
121.7 257.6
WASHINGTON TOWER
119.1 257.6
NOTE: RADAR required.
NOTE: Pilots shall comply with Ronald Reagan Washington Ntl Airport noise abatement and prohibited area (P-56) avoidance procedures as defined in Airport/Facility Directory special notices.
NOTE: ATC assigned only.
TOP ALTITUDE: 5000
WEST DEP CON
118.95 257.2
PROHIBITED AREA P-56 1.5 NM NORTH OF AIRPORT
P-56
R-328
R-070
R-185
EAST DEP CON
125.65 348.725
WESTMINSTER
117.9 EMI
Chan 126
WASHINGTON
111.0 DCA
Chan 47
ARMEL
113.5 AML
Chan 82
CASANOVA
116.3 CSN
Chan 110
LINDEN
114.3 LDN
Chan 90
GORDONSVILLE
115.6 GVE
Chan 103
MONTEBELLO
115.3 MOL
Chan 100
N
SWANN
SOOKI
AGARD
PALEO
DOCTR
WOOLY
HORTO
JERES
BUFFR
MCRAY
GINYA
RAMAY
OTTO
FLUKY
CLTCH
SCRAM
JDUBB
HAFNR
PAUKI
DAILY
WHINO
COLIN
TAKEOFF MINIMUMS
Rwy 1: 600-2 with minimum climb of 275' per NM to 1500 or standard with minimum climb of 460' per NM to 800.
Rwy 4: 300-2 or standard with minimum climb of 210' per NM to 400, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur not later than 1400' prior to DER.
Rwy 15: 300-1¾ or standard with minimum climb of 215' per NM to 400, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1500' prior to DER.
Rwy 19: 300-1½ or standard with minimum climb of 205' per NM to 300, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1200' prior to DER.
Rwy 22: 500-2¾ or standard with minimum climb of 305' per NM to 600.
Rwy 33: Standard with minimum climb of 285' per NM to 700.
NOTE: Chart not to scale.
(NARRATIVE ON FOLLOWING PAGE)
NE-3, 19 FEB 2026 to 19 MAR 2026