

LOC I-BRD
109.9

APP CRS
231°

Rwy Ldg
TDZE **1224**
Apt Elev **1232**

ILS or LOC RWY 23
BRainerd Lakes RGNL (BRD)

ADF required. When local altimeter setting not received, use Aitkin altimeter setting and increase all DAs 52 feet and all MDAs 60 feet. Increase S-LOC Cat C visibility to 1 SM and Circling Cat D visibility to 2¼ SM.

MALSRR

AS

MISSED APPROACH: Climb to 2100 then climbing right turn to 3000 direct LAREW LOM and hold.

ASOS
126.775

MINNEAPOLIS CENTER
118.05 239.0

UNICOM
122.7 (CTAF)

HUUTA
(RNAV 1-GPS REQD)

3000
(19.6)

MSA BR 25 NM

3100

ADF REQUIRED

LOCALIZER 109.9
I-BRD

LOM/IAF
LAREW
251 BR

BRNRD
(RNAV 1-GPS REQD)

18°

298°

BRNRD

051°

1 min

231°

1429

3000

358°

(6.6)

R-4301

2100

3000

BR

BR LOM

2976

051°

231°

3000

GS 3.00°

TCH 50

5.3 NM

CATEGORY	A	B	C	D
S-ILS 23	1424-½ 200 (200-½)			
S-LOC 23	1680-½	456 (500-½)	1680-¾ 456 (500-¾)	1680-1 456 (500-1)
CIRCLING	1760-1	528 (600-1)	1760-1½ 528 (600-1½)	1860-2 628 (700-2)

ELEV 1232

TDZE 1224

91

231°

7100 X 150

6512 X 150

34

5

☆

(H)

HIRL Rwy 5-23 and 16-34

REIL Rwy 5 and 16

FAF to MAP 5.3 NM

Knots

60 90 120 150 180

Min:Sec

5:18 3:32 2:39 2:07 1:46

BRainerd, Minnesota

Amdt 7A 29MAR18

46°24'N-94°08'W

BRainerd Lakes RGNL (BRD)

ILS or LOC RWY 23